

Dan Lopez

07 December 2018



### **PROJECT LOCATION**





#### WATER USE IN COPPER MINING

- Copper mining & processing
  - Concentrators (Flotation)
  - Electrowinning
  - Transportation
  - Dust suppression
- Limited fresh water supplies



### **ESCONDIDA WATER SUPPLY OVERVIEW**



#### **Water Production:**

- Marine Works 181 mgd hyd. cap
- SWRO 57 mgd initial phase
- Infrastructure sized for 91 mgd


#### Water Conveyance/Storage:

- 4 high pressure pump stations
- Two parallel pipelines, 110 mi long
- 129 MG Storage Reservoir


#### **Energy Infrastructure:**

- High voltage substations
- High voltage transmission lines

## **SEA WATER REVERSE OSMOSIS (SWRO) PROCESS**



## **Intakes and Outfall - Microtunneling**






### **Marine Works Sea Water Intake Structure Excavation**









## **Sea Water Intake and Brine Discharge Diffuser**





## **Sea Water Influent Pump Station Excavation**



Hard rock required blasting! >>> Mucho dinero



#### **9 Vertical Diffusion Vane Pumps**

- 9 pumps, each 540 l/s (8,560 gpm)
- 16m (52.5ft) pump column
- **Super Duplex Stainless Steel**
- 900 kW (1200 hp) motors
- Traveling Band Screens
  - Max flow rate = 4,256 L/s (97 MGD)
  - **Super Duplex Stainless Steel**



#### **Pretreatment: Dual Media Filtration**

- 2 Stages
  - 1<sup>st</sup> Stage: 36 pressure filters
  - 2<sup>nd</sup> Stage: 24 pressure filters
- Carbon Steel Vessels
  - 14 m (46 ft) total length
  - 4 m (13 ft) diameter
- Media: Anthracite/Sand
- Ferric chloride and polymer



#### **Reverse Osmosis**

- Horizontal Split Case high pressure pump, 540 l/s (8,560 gpm) at 75 bar (1100 psi)
- 9 RO racks (275 pressure vessels/rack)
- 270 l/s (4,280 gpm) permeate per RO Rack
- 50% Recovery

## **Construction: 2014 -2017**



## **As Modeled**



## **As Built**





# **Gracias!**

**Preguntas?**